


ISATY | LJLJLSR ūKS ōdzLwSŷu ū2 ō2kxā ūKS lYRdzŌUlyŌS ŌKlyeS āKlft ōS fSāā ūKlyŌxā 2f lYlæf ōlfdzS
 !YŋlSŷu ūSŷLJSŷlŭŭdzŷlS ōypc/кмлpc/ŷy ūKS LJLŷŷ ūSŷLJSŷlŭŭdzŷlS ōlYŋlSŷu ūSŷLJSŷlŭŭdzŷlS LJfdzā āSfŷŷSŷlŷlŭŭæy2f KSŷlŭ ūK2dzfŷr ōS dzyŷŷŷl mnpс/φ
 !YŋlSŷu ūSŷLJSŷlŭŭdzŷlS ōmnpс/ŷyŷL LJLŷŷ ūSŷLJSŷlŭŭdzŷlS ōlYŋlSŷu ūSŷLJSŷlŭŭdzŷlS LJfdzā āSfŷŷSŷlŷlŭŭæy2f KSŷlŭ ūK2dzfŷr ōS dzyŷŷŷl молс/φ



Soldering Reflow:



Preheat condition: 150 ~200 °C / 60~120 sec.


Allowed time above 217 °C : 60~150 sec.

Max temperature: 260 °C .

Allowed Reflow time: 3x max.


Packaging Information:

Tape Dimension:



Series	A0 (mm)	B0 (mm)	D (mm)	P0 (mm)	P1 (mm)	W (mm)	K0 (mm)	E (mm)	T (mm)
ACMA3225w	2N d y	3 l o y	1 l o y	l ø d l y	4 l y	8 l y	2N d o y	l N d o y	ø d o y

Peel force of top cover tape:






The force applied to the top cover tape

etwe f m j


o >



Reel Dimension: [mm]



Packaging Quantity:



1500 Pcs/Reel

5 Reel /Inner box(7.5K Pcs)

8 Inner box/Carton box(60K Pcs)

Cautions and Warnings:

Storage Conditions:

- The storage period is within 12 months after the completion of production. Be sure to follow the storage conditions (temperature: -5 to 35°C, humidity: 75% RH Max).If the storage period elapses, the soldering of the terminal electrodes may deteriorate.The warranty period is one year.
- Product should not be exposed to environment with high temperature, high humidity, dust, corrosive gas and etc.
- Products should be handled with care to avoid damage or contamination from perspiration and skin oils.
- Please always handle products carefully to prevent any damage caused by dropping down or inappropriate removing.

Operation Instructions:

- Self heating (temperature increase) occurs when the power is turned ON, so the tolerance should be sufficient for the set thermal design.
- Before soldering, be sure to preheat components.The preheating temperature should be set so that the temperature difference between the solder temperature and chip temperature does not exceed 150°C.
- Soldering corrections after mounting should be within the range of the conditions determined in the specifications.If overheated, a short circuit, performance deterioration, or lifespan shortening may occur.
- Generally, Koher might not be familiar with either customer's specific application or actual requests as customer does.As a result customer shall be responsible for checking and confirming whether Koher product with the performance described in the product specification is suitable for using in customer's particular application or not.