

- Flat wire coil for low copper losses
- $\frac{1}{2} Y_{LJ2\dot{a}2\dot{U}\dot{S}} \dot{O}2N\dot{S} Y\dot{I}\dot{U}\dot{S}N\dot{A}I\dot{f} I\dot{f}f2\dot{o}\dot{A} K\dot{I}\dot{E}K \dot{a}I\dot{U}d2N\dot{I}\dot{e}2y\dot{O}dzN\dot{N}I\dot{S}y\dot{U}\dot{a}$
- $\pm\dot{S}N\dot{U}\dot{e} t2\dot{o} \dot{I}\dot{O}dz\dot{a}\dot{o} y2\dot{I}\dot{a}\dot{S} I\dot{y}\dot{R} \dot{O}\dot{S}N\dot{U}\dot{e} t2\dot{o} \dot{f}\dot{S}I\dot{I}\dot{I}\dot{E}\dot{S} b\dot{d}z\dot{e} y2\dot{I}\dot{a}\dot{S}$
- High current cI-LJ-I-ÖIÜÜe I-yR KI-yRfSä KI EK ürl-yäI Syt current spi|es
- AE/πvHΛΛ Ijd2I-fäÜŠR
- hLJŠNI-əy3 ūSYLJŠNI-ūd2NŠ πpp ū2 bmp C öLyÖfdzRly3 äŠtf π ūSYLJŠNI-ūd2NŠ NjāŠu
- vdzI-yäÜÜeY HΛΛLJÖä

▪ 5/k5/ ŌzyŌŠNÚŠNā T2N ŠyŷŠNÚl·lyYŠyŷkyl·ŌłEłəZy äēäüŠYă
Noise supprŠāālZy for motorāy ōlyRākIšfR wiper



